



**ATS ELECTRO-LUBE**  
INTERNATIONAL INCORPORATED

## MD2000 TITAN CL™ Automatic Lubricator

The Electro-Luber MD 2000 TITAN CL™ Cartridge Luber is a powerful, motor-driven automatic lubricator which is refillable by simply replacing a standard grease cartridge. Its microprocessor controlled, energy efficient motor delivers grease to a fixed displacement pump which produces pressures up to 900psi. This strength allows the TITAN CL™ to drive lubricant through long feed lines, and to cycle progressive distributors to feed several bearings consecutively. When a valid dispensing cycle is selected, the unit will activate at selected intervals. At each interval, the TITAN CL™ dispenses approximately 1.25cc of grease. Neither temperature nor altitude will affect the output.



### FEATURES

- Most powerful lubricator on the market. Produces up to 900psi which enables it to service single-point applications up to 30' away (9 m.) and multi-point applications up to 20' (6 m.) away.
- Available with long-life replaceable battery packs or optional external power sources. (AC and DC)
- Optional Remote Control available to connect to customer supplied equipment or machinery (eg: PLC, Contactors, Relays)
- Multiple settings from 15 days to 2 years.
- Single or Multi-Point configuration
- Refillable using a standard grease cartridge (no other tools needed)
- Able to service up to 12 lube points with optional progressive distribution block
- Unit is mounted on an easy to install mounting plate
- Suitable for indoor/outdoor use
- LED operation and warning indicators:  
(1-RED, 1-GREEN, 1-BLUE)
  - 1 GREEN flash every 20 seconds  
– normal operation
  - 1 GREEN flash every second (approx.)  
– unit is dispensing grease
  - 1 RED flash every 20 seconds  
– limit switch error (unit operating in failsafe (timed dispense) mode)
  - 2 RED flashes every 20 seconds  
– Low Battery warning
  - 1 BLUE flash every 20 seconds  
– low grease level  
(grease cartridge needs to be replaced)

2 BLUE flashes every 20 seconds  
– unit is paused (remote control option)

4 BLUE flashes every 20 seconds  
– Low Temperature, dispensing is paused

### Temperature Range:

5°F. to 132°F. (-15°C. to 55°C.)  
(NOTE: Low Temp lubricant must be used at low temperatures)

### Size:

24.5" h X 6" w X 8" d  
(62cm. h X 15cm. w X 20cm. d)



MADE IN CANADA

[www.atselectrolube.com](http://www.atselectrolube.com)

BUS: (604) 946-1308 FAX: (604) 946-0427 TOLL FREE PHONE: 1-800-663-8141 TOLL FREE FAX: 1-800-663-8140  
7388 Wilson Avenue, Delta, British Columbia, Canada V4G 1H3